

# KUZCO LIGHTING

## LUMINAIRE PHOTOMETRIC REPORT

**Filename:** PD22332-BN - Ampersand

**Manufacturer:** Kuzco Lighting

**Luminaire:** AMPERSAND / CEILING MOUNT

**Luminaire Cat:** PD22332-BN

**Lamp:** LED W/ DRIVER

**Lamp Cat:** UNKNOWN

**Ballast Desc:** DR-CC-40; IN: 100-130VAC,0.42A; OUT: 31-44VDC, 900mA (const), 40W (max)

**Ballast Cat:** HUEUC DR-CC-40 (x2)

**Lamp Output:** Total luminaire Lumens: 3343.9

**Max Candela:** 840.2 at Horizontal: 110°, Vertical: 7.5°

**Input Wattage:** 67.4

**Luminous Opening:** Circular (Dia: 32.01")

**Test:** 1305-19


**Test Date:** 12 March 2019

**Test Lab:** Kuzco Lighting

**Photometry :** Type C

**CIE Class:** Semi-Direct

**Cutoff Class:** Noncutoff



### Zonal Lumen Summary

Zone	Lumens	% Luminaire
0-30	647.8	19.4%
0-40	1,069.9	32%
0-60	1,970.6	58.9%
60-90	968.3	29%
70-100	704.8	21.1%
90-120	312.5	9.3%
0-90	2,938.9	87.9%
90-180	405.1	12.1%
0-180	3,343.9	100%

### Lumens Per Zone

Zone	Lumens	% Total	Zone	Lumens	% Total
0-10	78.1	2.3%	90-100	141.7	4.2%
10-20	225.4	6.7%	100-110	99.2	3%
20-30	344.3	10.3%	110-120	71.6	2.1%
30-40	422.1	12.6%	120-130	39.5	1.2%
40-50	454.5	13.6%	130-140	22.9	0.7%
50-60	446.1	13.3%	140-150	13.8	0.4%
60-70	405.2	12.1%	150-160	8.9	0.3%
70-80	334.9	10.0%	160-170	5.5	0.2%
80-90	228.2	6.8%	170-180	1.9	0.1%

