

# KUZCO LIGHTING

## LUMINAIRE PHOTOMETRIC REPORT

**Filename:** 401432BN-LED - Cameo

**Manufacturer:** Kuzco Lighting

**Luminaire:** Pendant

**Luminaire Cat:** 401432BN-LED

**Lamp:** 120V LED

**Lamp Cat:** DIS 02-800-930-120-S3

**Lamp Output:** Total luminaire Lumens: 368.3

**Max Candela:** 164.2 at Horizontal: 330°, Vertical: 10°

**Input Wattage:** 10

**Luminous Opening:** Circular (Dia: 3.86")

**Test:** 076\_15

**Test Date:** 10 September 2015

**Test Lab:** Kuzco Lighting

**Photometry :** Type C


**CIE Class:** Direct

**Cutoff Class:** Cutoff

**Nema Type:** 7 X 7


### Zonal Lumen Summary

Zone	Lumens	% Luminaire
0-30	111.7	30.3%
0-40	171.2	46.5%
0-60	277.7	75.4%
60-90	63.0	17.1%
70-100	29.4	8%
90-120	8.2	2.2%
0-90	340.7	92.5%
90-180	27.6	7.5%
0-180	368.3	100%



### Lumens Per Zone

Zone	Lumens	% Total	Zone	Lumens	% Total
0-10	13.0	3.5%	90-100	2.0	0.5%
10-20	41.8	11.3%	100-110	2.4	0.7%
20-30	56.9	15.4%	110-120	3.7	1%
30-40	59.5	16.2%	120-130	6.1	1.7%
40-50	57.9	15.7%	130-140	5.6	1.5%
50-60	48.6	13.2%	140-150	4.2	1.1%
60-70	35.6	9.7%	150-160	2.4	0.7%
70-80	21.0	5.7%	160-170	1.0	0.3%
80-90	6.4	1.7%	170-180	0.2	0%



**Illuminance at a Distance**

	Center Beam fc	Beam Width	
1.5ft	54.1 fc	2.7 ft	2.6 ft
3.0ft	13.5 fc	5.4 ft	5.2 ft
4.5ft	6.01 fc	8.1 ft	7.7 ft
6.0ft	3.38 fc	10.8 ft	10.3 ft
7.5ft	2.16 fc	13.5 ft	12.9 ft
9.0ft	1.50 fc	16.2 ft	15.5 ft

Legend:  
 Vert. Spread: 84.1°  
 Horiz. Spread: 81.4°

**Coefficients Of Utilization - Zonal Cavity Method**

Effective Floor Cavity Reflectance: 20%

RCC %:	<b>80</b>				<b>70</b>				<b>50</b>			<b>30</b>			<b>10</b>			<b>0</b>
RW %:	<u>70</u>	<u>50</u>	<u>30</u>	<u>0</u>	<u>70</u>	<u>50</u>	<u>30</u>	<u>0</u>	<u>50</u>	<u>30</u>	<u>20</u>	<u>50</u>	<u>30</u>	<u>20</u>	<u>50</u>	<u>30</u>	<u>20</u>	<u>0</u>
RCR: 0	1.17	1.17	1.17	1.17	1.14	1.14	1.14	.92	1.07	1.07	1.07	1.01	1.01	1.01	.95	.95	.95	.92
1	1.08	1.03	.99	.95	1.04	1.00	.96	.79	.94	.91	.89	.89	.87	.85	.85	.83	.81	.78
2	.98	.90	.84	.79	.95	.88	.82	.67	.83	.78	.74	.79	.75	.71	.75	.72	.69	.66
3	.90	.80	.72	.66	.87	.78	.71	.58	.74	.68	.63	.70	.65	.61	.67	.63	.59	.57
4	.83	.71	.63	.57	.80	.70	.62	.51	.66	.60	.54	.63	.57	.53	.60	.55	.51	.49
5	.76	.64	.56	.49	.74	.63	.55	.45	.60	.53	.47	.57	.51	.46	.54	.49	.45	.43
6	.71	.58	.49	.43	.68	.57	.49	.40	.54	.47	.42	.52	.46	.41	.50	.44	.40	.38
7	.66	.53	.44	.39	.64	.52	.44	.36	.50	.43	.37	.47	.41	.37	.46	.40	.36	.34
8	.61	.48	.40	.35	.59	.47	.40	.32	.45	.39	.34	.44	.38	.33	.42	.37	.32	.31
9	.57	.45	.37	.31	.56	.44	.36	.29	.42	.35	.31	.40	.34	.30	.39	.34	.29	.28
10	.54	.41	.34	.29	.52	.40	.33	.27	.39	.32	.28	.38	.32	.27	.36	.31	.27	.25



**Luminaire Report Summary**

IESNA:LM-63-2002  
[TEST] 076\_15  
[TESTLAB] Kuzco Lighting  
[TESTDATE] 10 September 2015  
[ISSUEDATE] 2015-09-10 15:31:53  
[NEARFIELD]  
[LAMPPOSITION] 0,0  
[OTHER] EVERFINE GO-2000A\_V1 SYSTEM  
[MANUFAC] Kuzco Lighting  
[LUMCAT] 401432BN-LED  
[LUMINAIRE] Pendant  
[LAMPCAT] DIS 02-800-930-120-S3  
[LAMP] 120V LED

FILE: CREATED USING ABSOLUTE PHOTOMETRY  
FILE: CANDELA MULTIPLIER: 1  
FILE: VERTICAL ANGLES: 37, HORIZONTAL ANGLES: 37  
FILE: COORDINATE SYSTEM: TYPE C  
FILE: UNIT OF MEASURE: METRIC  
FILE: BALLAST FACTOR: 1

Photometrics Pro 1.3.29 copyright 2003-2020 by jSolutions, Inc.  
Reported data calculated from manufacturer's data file, based on IES recommended methods.