

# KUZCO LIGHTING

## LUMINAIRE PHOTOMETRIC REPORT

**Filename:** EW67206-BK - Runyon

**Manufacturer:** KUZCO LIGHTING

**Luminaire:** CEILING/FLUSH MOUNT

**Luminaire Cat:** EW67206-BK

**Lamp:** DC LED w/ DRIVER

**Lamp Cat:** DC LED

**Ballast Desc:** In:120-277VAC, 0.2A: Output: 24-40VDC, 500mA, 20W

**Ballast Cat:** HEP LSC20W500P-UNI

**Lamp Output:** Total luminaire Lumens: 443.1

**Max Candela:** 303.0 at Horizontal: 0°, Vertical: 0°

**Input Wattage:** 9.4

**Luminous Opening:** (L: 9.84", W: 9.84", H: 0")

**Test:** 1375-19

**Test Date:** 12 November 2019

**Test Lab:** KUZCO LIGHTING

**Photometry :** Type C

**CIE Class:** General Diffuse




**Cutoff Class:** Noncutoff

### Zonal Lumen Summary

Zone	Lumens	% Luminaire
0-30	161.3	36.4%
0-40	206.3	46.6%
0-60	217.6	49.1%
60-90	3.9	0.9%
70-100	3.4	0.8%
90-120	3.9	0.9%
0-90	221.6	50%
90-180	221.5	50%
0-180	443.1	100%

### Lumens Per Zone

Zone	Lumens	% Total	Zone	Lumens	% Total
0-10	25.4	5.7%	90-100	1.1	0.2%
10-20	59.8	13.5%	100-110	1.2	0.3%
20-30	76.1	17.2%	110-120	1.6	0.4%
30-40	45.1	10.2%	120-130	2.5	0.6%
40-50	8.9	2.0%	130-140	8.9	2%
50-60	2.5	0.6%	140-150	45.0	10.2%
60-70	1.6	0.4%	150-160	76.1	17.2%
70-80	1.2	0.3%	160-170	59.8	13.5%
80-90	1.1	0.2%	170-180	25.3	5.7%



Photometrics Pro 1.3.29 copyright 2003-2020 by jSolutions, Inc.  
Reported data calculated from manufacturer's data file, based on IES recommended methods.