

KUZCO LIGHTING

LUMINAIRE PHOTOMETRIC REPORT

Filename: LP14935-WH - Chute

Manufacturer: KUZCO LIGHTING

Luminaire: Linear Pendant

Luminaire Cat: LP14935-WH

Lamp: DC LED w/ Driver

Lamp Cat: N/A

Ballast Desc: IN:100-130VAC 50/60Hz,0.21A;OUT:31-44VDC,400mA, 20W(max)

Ballast Cat: HUEUC DC-CC-20

Lamp Output: Total luminaire Lumens: 783.5

Max Candela: 214.8 at Horizontal: 270°, Vertical: 0.5°

Input Wattage: 16.4

Luminous Opening: Rectangle (L: 0.79", W: 35.83")

Test: 1360-19

Test Date: 10 October 2019

Test Lab: KUZCO LIGHTING

Photometry : Type C


CIE Class: Direct

Cutoff Class: Noncutoff

Nema Type: 7 X 7



Zonal Lumen Summary

Zone	Lumens	% Luminaire
0-30	164.4	21%
0-40	271.2	34.6%
0-60	495.4	63.2%
60-90	221.6	28.3%
70-100	158.6	20.2%
90-120	59.6	7.6%
0-90	717.0	91.5%
90-180	66.5	8.5%
0-180	783.5	100%



Lumens Per Zone

Zone	Lumens	% Total	Zone	Lumens	% Total
0-10	19.9	2.5%	90-100	32.5	4.1%
10-20	57.2	7.3%	100-110	18.4	2.3%
20-30	87.3	11.1%	110-120	8.7	1.1%
30-40	106.8	13.6%	120-130	3.4	0.4%
40-50	114.2	14.6%	130-140	1.2	0.2%
50-60	109.9	14.0%	140-150	0.9	0.1%
60-70	95.5	12.2%	150-160	0.7	0.1%
70-80	74.4	9.5%	160-170	0.5	0.1%
80-90	51.7	6.6%	170-180	0.2	0%



Reported data calculated from manufacturer's data file, based on IES recommended methods.