

# KUZCO


## LIGHTING

### LUMINAIRE PHOTOMETRIC REPORT

**Filename:** PD15824-BK - Taper  
**Manufacturer:** KUZCO LIGHTING  
**Luminaire:** CEILING MOUNT/PENDANT  
**Luminaire Cat:** PD15824-BK  
**Lamp:** DC LED  
**Lamp Cat:** Unknown  
**Ballast Desc:** IN: 120VAC, 0.6A; OUT: 30-40VDC, 130mA  
**Ballast Cat:** NOCVO NE007040013-2G  
**Lamp Output:** Total luminaire Lumens: 418.9  
**Max Candela:** 1,635.7 at Horizontal: 0°, Vertical: 0°  
**Input Wattage:** 6.7  
**Luminous Opening:** Circular (Dia: 0.04")  
**Test:** 1431-20  
**Test Date:** 04 February 2020  
**Test Lab:** KUZCO LIGHTING  
**Photometry :** Type C  
**CIE Class:** Direct  
**Cutoff Class:** Cutoff  
**Nema Type:** 4 X 4

#### Zonal Lumen Summary

Zone	Lumens	% Luminaire
0-30	368.5	88%
0-40	398.5	95.1%
0-60	413.4	98.7%
60-90	0.7	0.2%
70-100	0.5	0.1%
90-120	0.7	0.2%
0-90	414.1	98.9%
90-180	4.7	1.1%
0-180	418.9	100%



#### Lumens Per Zone

Zone	Lumens	% Total	Zone	Lumens	% Total
0-10	124.3	29.7%	90-100	0.2	0%
10-20	167.8	40.1%	100-110	0.2	0.1%
20-30	76.4	18.2%	110-120	0.3	0.1%
30-40	30.0	7.2%	120-130	0.5	0.1%
40-50	11.2	2.7%	130-140	0.7	0.2%
50-60	3.7	0.9%	140-150	1.0	0.2%
60-70	0.4	0.1%	150-160	0.9	0.2%
70-80	0.2	0.0%	160-170	0.7	0.2%
80-90	0.1	0.0%	170-180	0.2	0.1%

