

KUZCO LIGHTING

LUMINAIRE PHOTOMETRIC REPORT

Filename: PD86132-WH - Cerchio

Manufacturer: KUZCO LIGHTING

Luminaire: CEILING MOUNT / PENDANT

Luminaire Cat: PD86132-WH

Lamp: DC LED w/ Driver

Lamp Cat: DC LED

Ballast Desc: IN: 120-277VAC, 0.68A; OUT: 43-86VDC, 06A (const) 51.6W (max)

Ballast Cat: DONE DL-50W600-LP

Lamp Output: Total luminaire Lumens: 3485.9

Max Candela: 587.9 at Horizontal: 150°, Vertical: 1°

Input Wattage: 72

Luminous Opening: Circular (Dia: 32.28")

Test: 1385-19


Test Date: 21 November 2019

Test Lab: KUZCO LIGHTING

Photometry : Type C

CIE Class: General Diffuse

Cutoff Class: Noncutoff



Zonal Lumen Summary

Zone	Lumens	% Luminaire
0-30	457.2	13.1%
0-40	751.2	21.6%
0-60	1,339.5	38.4%
60-90	403.1	11.6%
70-100	235.5	6.8%
90-120	403.0	11.6%
0-90	1,742.6	50%
90-180	1,743.3	50%
0-180	3,485.9	100%

Lumens Per Zone

Zone	Lumens	% Total	Zone	Lumens	% Total
0-10	55.6	1.6%	90-100	50.8	1.5%
10-20	159.4	4.6%	100-110	133.9	3.8%
20-30	242.3	7.0%	110-120	218.3	6.3%
30-40	294.0	8.4%	120-130	280.6	8.1%
40-50	307.5	8.8%	130-140	307.7	8.8%
50-60	280.7	8.1%	140-150	294.3	8.4%
60-70	218.4	6.3%	150-160	242.6	7%
70-80	133.9	3.8%	160-170	159.5	4.6%
80-90	50.8	1.5%	170-180	55.6	1.6%

