

# KUZCO

## LIGHTING

### LUMINAIRE PHOTOMETRIC REPORT

**Filename:** WS13760-WH - Lever

**Manufacturer:** KUZCO LIGHTING

**Luminaire:** Wall Sconce

**Luminaire Cat:** WS13760-WH

**Lamp:** LED w/ Driver

**Lamp Cat:** Unknown

**Lamp Output:** Total luminaire Lumens: 1073.1

**Max Candela:** 356.9 at Horizontal: 180°, Vertical: 107.5°

**Input Wattage:** 29.9

**Luminous Opening:** Rectangle (L: 58.66", W: 0.39")

**Test:** 1200\_18

**Test Date:** 16 October 2018


**Test Lab:** KUZCO LIGHTING

**Photometry :** Type C

**CIE Class:** Semi-Indirect

**Cutoff Class:** Noncutoff

**Nema Type:** 7 X 5




#### Zonal Lumen Summary

Zone	Lumens	% Luminaire
0-30	6.2	0.6%
0-40	21.5	2%
0-60	104.8	9.8%
60-90	278.3	25.9%
70-100	325.3	30.3%
90-120	360.4	33.6%
0-90	383.1	35.7%
90-180	690.1	64.3%
0-180	1,073.1	100%

#### Lumens Per Zone

Zone	Lumens	% Total	Zone	Lumens	% Total
0-10	0.2	0.0%	90-100	120.6	11.2%
10-20	1.0	0.1%	100-110	122.8	11.4%
20-30	4.9	0.5%	110-120	117.0	10.9%
30-40	15.4	1.4%	120-130	103.9	9.7%
40-50	31.5	2.9%	130-140	85.5	8%
50-60	51.8	4.8%	140-150	64.3	6%
60-70	73.6	6.9%	150-160	43.1	4%
70-80	94.1	8.8%	160-170	24.6	2.3%
80-90	110.6	10.3%	170-180	8.2	0.8%



**Illuminance at a Distance**

	Center Beam fc	Beam Width
1.5ft	0.90 fc	4.6 ft 4.8 ft
3.0ft	0.22 fc	9.1 ft 9.7 ft
4.5ft	0.10 fc	13.7 ft 14.5 ft
6.0ft	0.06 fc	18.2 ft 19.3 ft
7.5ft	0.04 fc	22.8 ft 24.1 ft
9.0ft	0.02 fc	27.3 ft 29.0 ft

■ Vert. Spread: 113.2°  
■ Horiz. Spread: 116.3°