Ceiling Pendant

494502M

START FROM HERE

- Make sure power is completely off at the fuse box.
- · Have your fixture installed by a qualified licensed electrician
- Prepare everything in a clear area.
- Wear gloves at all times during this installation.
- Read instructions carefully before you start assembly.
- Keep this instruction sheet for future reference.

Technical Support: 1-855-855-8926

Please Note:

• 120V input

- 1. Remove the fixture from its original packaging
- 2. Remove the mounting plate (1c) from the canopy (2a) by removing the decorative nuts (2c)
- **3.** Align mounting plate screws (1d) to desired orientation, and then attach mounting plate (1c) to electrical junction box (1a) using junction box screws provided (1e) in hardware package
- **4.** To change fixture height, shorten or lengthen wire by removing screw **(2b)** from canopy **(2a)** and push or pull wire to your desired length. Secure screw **(2b)** in canopy **(2a)** to lock wire in place
- **5.** Make proper electrical connections (black to hot "L", white to neutral "N", ground to "GND") with wire nuts (1b) provided in hardware package
- **6.** Align and insert mounting plate screws (1d) through holes on canopy (2a), secure with decorative nuts (2c)
- Install bulb into the fixture (bulb not included) and pull up fixture socket (3b) into the fixture (3a). Then install the ring (3c) on bulb to secure and thread on fixture end (3d) to close



