Please Note:

• 120V input

3b.

## START FROM HERE

- Make sure **POWER** is **COMPLETELY OFF** at the fuse box
- Have your fixture installed by a qualified licensed electrician
- Prepare everything in a clear area
- Wear gloves at all times during this installation
- · Read instructions carefully before you start assembly
- Keep this installation sheet for future reference

**Technical Support:** 1-855-855-8926

- 1. Remove fixture from its original package
- 2. Attach crossbar (1c) to electrical junction box (1a) using junction box screws (1e) provided in hardware package
- **3.** Make proper electrical connections (**black** to **hot** "L", **white** to **neutral** "N", **ground** to "**GND**") with wire nuts (**1b**) provided in hardware package
- 4. Install Pan-Head Crossbar Mounting Screws (1d) halfway into threaded holes on crossbar (1c). Align keyholes on backplate (2a) to Pan-Head Crossbar Mounting Screws (1d) heads, insert and turn, and then secure with screw driver
- 5. Insert bulb (4a) into fixture socket
- **6.** Gently pull back clips **(2b)** to secure glass **(3a)** onto backplate **(2a)**, followed by the ring **(3b)** until it clicks into place **(Note:** do not apply too much pressure, as excessive pressure will cause the glass to crack or break)

