LED Exterior Pendant

EP26608

START FROM HERE

- Make sure POWER is COMPLETELY OFF at the fuse box
- Have your fixture installed by a qualified licensed electrician
- Prepare everything in a clear area
- Wear gloves at all times during this installation
- Read instructions carefully before you start assembly
- Keep this installation sheet for future reference

Technical Support: 1-855-855-8926

- 1. Remove fixture from its original package
- 2. Separate mounting plate (1c) from canopy (2d) by removing decorative nuts (2c)
- **3.** Align mounting plate screws **(1d)** to desired orientation, and then attach mounting plate **(1c)** to electrical junction box **(1a)** using junction box screws provided **(1e)** in hardware package
- **4.** To change fixture height, use set screw (2b), slide wire to desired length and tighten with allen key (2b)
- Make proper electrical connections (black to hot "L", white to neutral "N", ground to "GND") with wire nuts (1b) provided in hardware package
- **6.** Align and insert mounting plate screws (1d) through holes on canopy (2d), secure with decorative nuts (2c)
- 7. To prevent moisture from entering the electrical junction box (1a) and causing a short, seal around the top perimeter between the fixture and the surface with weather resistant caulking (Illustration 1).

PRODUCT ID	PART
1e.	XHPP832-8
1c.	XHBCS412-GV
1d.	XHPP832-4
2b.	XHSS832-2
2c.	XHDN832-1/4-(color)
2d.	XHCNPCC-412-38-(color)
LED	XLED-EDC20-830-120-ELV
Allen Key	XHAK-832

 $K \cup Z \cap Q$

19054 28th Avenue Surrey, BC Canada V3Z 6M3 T: 604 538 7162 TF: 1-855 85 KUZCO F: 604 538 7196 W: kuzcolighting.com 20200108

Please Note:

- This Kuzco LED fixture comes with pre-wired LED module(s)
- Unless instructed, Do Not touch any part of the LED module(s) as any unnecessary contact with the module could cause permanent damage
- For dimming, an ELV (Electronic Low Voltage) type of dimmer is required
- Must be installed on a covered ceiling
- 120V input

