LED Linear Pendant

LP28543

START FROM HERE

- $\ensuremath{\cdot}$ Make sure $\ensuremath{\mathsf{POWER}}$ is $\ensuremath{\mathsf{COMPLETELY}}$ OFF at the fuse box
- Have your fixture installed by a qualified licensed electrician
- Prepare everything in a clear area
- Wear gloves at all time during this installation
- Read instructions carefully before you start assembly
- Keep this installation sheet for future reference


Technical Support: 1-855-855-8926

- 1. Remove fixture from its original package
- 2. Separate mounting plate (1c) from canopy (2a) by removing canopy screws (2b)
- Attach mounting plate (1c) to electrical junction box (1a) using junction box screws provided (1e) in hardware package
- Attach glass (3f) to fixture (3b) with decorative bar (3e) and secure with screws (3d)
- Place washer (3c), followed by connector (3a) onto fixture (3b) and thread clockwise to secure (See Illustration 1)

6.

Make proper electrical connections (**black** to **hot** "L", **white** to **neutral** "N", **ground** to "**GND**") with wire nuts (**1b**) provided in hardware package and place driver (**4a**) inside canopy (**2a**)

- 7. Attach canopy (2a) to mounting plate (1c) with canopy screws (2b)
- **8.** Mark and install ceiling gripper barrel (**5a**) with screw (**5b**). Secure aircraft barrel (**5c**) to ceiling gripper barrel (**5a**) by threading clockwise. Ideal distance between aircraft barrels (**5c**) is 41-5/16"
- **9.** Fine tone wire length if necessary, by push and hold wire gripper (2g) and then adjust wire to desired length



KUZCO

19054 28th Avenue Surrey, BC Canada V3Z 6M3 T: 604 538 7162 TF: 1-855 85 KUZCO F: 604 538 7196 W: kuzcolighting.com 20231003

Please Note:

- This Kuzco LED fixture comes with pre-wired LED module(s)
- Unless instructed, Do Not touch any part of the LED module(s) as any unnecessary contact with the module could cause permanent damage
- Use ELV (Electronic Low Voltage) or TRIAC type of dimmer for dimming application
- 120V input

