## **LED Linear Pendant**

## INSTALLATION SHEET

## START FROM HERE

- Make sure POWER is COMPLETELY OFF at the fuse box
- Have your fixture installed by a qualified licensed electrician
- · Prepare everything in a clear area
- · Wear gloves at all times during this installation
- · Read instructions carefully before you start assembly
- · Keep this installation sheet for future reference

**Technical Support:** 1-855-855-8926

## Please Note:

- This Kuzco LED fixture comes with pre-wired LED module(s)
- Unless instructed, Do Not touch any part of the LED module(s) as any unnecessary contact with the module could cause permanent damage
- For dimming, an ELV (Electronic Low Voltage) or TRIAC type of dimmer is required
- 120V input

Remove fixture from its original package
Separate mounting plate (1c) from canopy (2a) by removing the canopy screws (2b)
Attach mounting plate (1c) to electrical junction box

Attach mounting plate (1c) to electrical junction box (1a) using junction box screws provided (1e) in hardware package

**4.** Secure mounting plate (1c) to mounting surface with anchors (1f) and screws (1g)

**5.** Determine hanging height of fixture by securing rods (2d) to canopy pivot (2c) and fixture body (3a) and attach canopy pivot (2c) to canopy (2a) with washer (5b) and nut (5a), after feeding fixture wires (LED+ and LED-) through rods

**6.** Make proper electrical connections between LED and DC driver, LED- Negative, LED+ Positive using quick connector provided (See Illustration 1 and refer to diagram on driver)

Make proper electrical connections (black to hot "L", white to neutral "N", ground to "GND") with wire nuts (1b) provided in hardware package and place driver (4a) inside canopy (2a)

**8.** Attach fixture bars (3a) together and secure with plate (3b) and screws (3c) (See Illustration 2)

**9.** Slide fixture side plates (5a) along fixture bar (3a), secure with side plate screws (5b). Secure fixture side plates (5a) together with decorative nuts (5c) and screws (5d). Attach fixture top plates (6a) to fixture side plates (5a) with decorative nuts (6b) and screws (6c)

**10.** Secure canopy **(2a)** to mounting plate **(1c)** with canopy screws **(2b)** 



