## **Incandescent Pendant**

Please Note:

• 120V input

## START FROM HERE

- Make sure **POWER** is **COMPLETELY OFF** at the fuse box
- Have your fixture installed by a qualified licensed electrician
- Prepare everything in a clear area
- Wear gloves at all times during this installation
- · Read instructions carefully before you start assembly
- Keep this installation sheet for future reference

**Technical Support:** 1-855-855-8926

- **1.** Remove fixture from its original package
- 2. Separate mounting plate (1c) from canopy (2a) by removing canopy screws (2b)
- **3.** Attach mounting plate (1c) to electrical junction box (1a) using junction box screws provided (1e) in hardware package
- 4. To change fixture height, shorten or lengthen wire by removing screw (2c) from wire lock (5b) and push or pull wire to your desired length. Secure screw (2c) in wire lock (5b) to lock wire in place and place wire lock (5b) inside canopy (2a).
- **5.** Make proper electrical connections (**black** to **hot** "L", **white** to **neutral** "N", **ground** to "**GND**") with wire nuts (**1b**) provided in hardware package
- **6.** Attach canopy **(2a)** to mounting plate **(1c)** with canopy screws **(2b)**
- Attach shade (3b) to fixture (3a) and secure with washer (3c) and shade connector (3d) using wrench (5a)
- 8. Insert bulb (4a) into fixture socket

